

Stoner Molding
Solutions®
You Mold It. We Release It.™

Stoner® E702 Rocket Release®

Food Grade Release Agent



Product Description

Stoner® 702 Rocket Release® is an extremely versatile release agent which is generally acceptable for applications where a food grade release is required. In many applications, Rocket Release is considered to be the “most paintable” release agent available when molding plastics and similar materials. Rocket Release allows molded parts to be painted, plated, hotstamped, adhesive bonded, labelled, or otherwise decorated in most applications. Provides a long lasting anti-stick film for fast, easy part removal from molds and multiple part releases per application. Improves molding efficiency in many processes including injection, vacuum form, and pour cast molding. Economical – a light coating produces best results.

E702 Rocket Release® ADVANTAGES:

- Allows molded parts to be painted, hotstamped, or otherwise decorated.
- The release agent in E702 meets FDA regulation 21 CFR 184.1400 as a release agent in the manufacture of food contacting materials.
- Improves part appearance and reduces defects caused by sticking.
- Formulated to provide high levels of user and environmental safety.
- Contains no chlorinated solvents such as 1,1,1 trichloroethane, trichloroethylene, or methylene chloride.
- Colorless and non-staining.

Uses

Stoner® E702 Rocket Release® is an extremely versatile release agent for molding:

- Food grade
- Paintable
- Plastics

Directions for Use

Recommended Procedure

Read entire label and Material Safety Data Sheet before using. Use this cylinder with Stoner hose/sprayer assembly.

TO CONNECT SPRAYHEAD/VALVE TO SPRAYER ASSEMBLY:

Place selected plastic aerosol sprayhead into opening on metal aerosol valve. Unscrew knurled cap of sprayer assembly. Place metal aerosol valve on sprayer body with O-ring seated between metal aerosol valve and rim of sprayer body. Place knurled cap over valve and hand tighten firmly to seat O-ring seal.

TO CONNECT HOSE/SPRAYER ASSEMBLY:

With cylinder valve closed, attach male fitting on hose to female opening on sprayer assembly and female end of hose to threaded male fitting on cylinder. Open cylinder valve only after hose and sprayer connections are connected and tightened firmly with wrench. Opening valve when connections are loose may result in leakage and damage or injury. For returnable cylinders, attach female end of hose to male fitting on “liquid” side of valve (usually the “red” handle).

WHEN DISCONNECTING HOSE/SPRAYER ASSEMBLY: Close valve on cylinder by turning clockwise. Release any remaining pressure in hose/sprayer assembly by depressing sprayhead until spray stops completely. Slowly disconnect hose from cylinder valves.

TO USE PRODUCT: TANK MUST BE POSITIONED WITH LABEL ARROWS POINTING UP. Be sure all hose and sprayer assembly connections are tightened firmly. Open cylinder valve slowly. Hold sprayer 10 to 12 inches from surface to be sprayed. Apply a thin mist coating on surface for best results. Close cylinder valve after using.

Storage and Handling

Do not puncture or incinerate container. Do not expose container to heat or store at temperatures above 120 °F. Keep container away from and do not use near sparks, open flame, heated surfaces, or other ignition sources.

Packaging

Stoner® E702 Rocket Release® is available in:

- | | |
|-----------------------------|---------------|
| • 31-pound Giant Aerosol | Part # E702 |
| • 12-can case of 12 oz cans | Part # E302 |
| • 5-gallon pails | Part # M302PL |
| • 55-gallon drum | Part # M302DR |

Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355

Email: CustomerService@StonerMolding.com

Visit: StonerMolding.com

NO RISK GUARANTEE. Stoner Molding guarantees 100% satisfaction or your money back. If you're ever dissatisfied with any Stoner Molding product, simply return the unused portion for a full refund.



StonerMolding.com

1070 Robert Fulton Hwy. • Quarryville, PA 17566 • 1-800-227-5538 • 1-717-786-7355

Made
in USA