

Safety Data Sheet

A353 Endurance™ Mold Release

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Endurance™ Mold Release
Product Code: A353
Product Use: Mold Release
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Flammable Aerosol Category 1
Gases under pressure - Liquefied Gas
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Danger

Hazard Statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302+P352 - If on skin: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
P312 - Call a poison center, doctor or medical center if you feel unwell.
P321 - Specific treatment (see on this SDS).
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>Percent</u>
Petroleum distillates	64741-65-7	60 - 80
Hydrocarbon propellant	68476-86-8	20 - 40
Dimethyl carbinol	67-63-0	1-20
Lubricant	71750-79-3	1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 1	Flammability: 4	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; liver;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. Avoid prolonged or repeated contact with skin. This material can be harmful or irritating. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated breathing of vapor. Do not use near ignition sources. If ventilation is not sufficient, wear proper respiratory equipment. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Do not store at temperatures above 122 degrees F. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Ventilation is required to maintain operator exposure below published exposure limits. Local exhaust should be used in areas where exposure limits may be exceeded.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Petroleum distillates	64741-65-7	100 ppm TWA	500 ppm	Not established
Hydrocarbon propellant	68476-86-8	1000ppm	Not established	Not established
Dimethyl carbinol	67-63-0	400 ppm	Not established	500 ppm STEL
Lubricant	71750-79-3	Not established	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Light Hydrocarbon	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H ₂ O=1):	0.7
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	500
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	80 - 100		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acetaldehyde. Acids. Chlorine. Ethylene oxide. Isocyanates.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Dimethyl carbinol	67-63-0	DERMAL LD50 Rabbit 12800 mg/kg ORAL LD50 Mouse 3600 mg/kg ORAL LD50 Rat 5000 mg/kg INHALATION LC50 Rat 16000 ppm INHALATION LC50 Mouse 53000 MG/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available
Mobility:	No data available This material (or one of its components), dissolves in water. If it enters the soil, it will be highly mobile and may contaminate ground water.

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Petroleum distillates	64741-65-7	Aquatic LC50 Bl gill > 1000 mg/L 24HR EC50 Daphnia > 1000 mg/L 24HR EC50 AQUATIC PLANTS > 1000 mg/L
Dimethyl carbinol	67-63-0	Aquatic LC50 (96h) MINNOW = 9640 mg/L 24HR EC50 Daphnia > 10000 mg/L No data available

13. DISPOSAL CONSIDERATIONS

Disposal :	Dispose according to Federal, State and local regulations.
------------	--

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 07/28/2020

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.