

Safety Data Sheet

ME-5050NS/A590 Corrosion Preventive



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Corrosion Preventive
Product Code: ME-5050NS/A590
Product Use: Corrosion Preventive
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Gases under pressure - Liquefied Gas
Aspiration Hazard Category 1
Flammable Aerosol Category 2
Skin Corrosion/Irritation Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Danger

Hazard Statements

Flammable aerosol.
Contains gas under pressure; may explode if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.
P302+P352 - If on skin: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a poison center, doctor or medical center if you feel unwell.
P321 - Specific treatment (see on this SDS).
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>Percent</u>
Aliphatic hydrocarbons	142-82-5	40 - 60
Ether propellant	115-10-6	20 - 40
Glycol ether	1569-01-3	1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 2	Flammability: 3	Physical: 1	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse. For liquid contact, treat for frostbite if necessary.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; central nervous system; auditory system; arrhythmias (irregular heartbeats); liver; eye.

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous. Containers may rupture or explode under fire conditions.
Fire Fighting Instructions:	Use CO ₂ , foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Do not store at temperatures above 122 degrees F. Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Ether propellant	115-10-6	Not established	Not established	1,000 ppm 8 & 12 hr. TWA (Mfr.)
Glycol ether	1569-01-3	Not established	Not established	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Brown	Upper Flammability Limit (%):	Not applicable
Odor:	Petroleum solvent	Vapor Pressure (PSIG @ 70°F):	62.0
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H2O=1):	0.73
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	0.07 at 25 °C (77 °F)
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	474.8
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	80 - 100		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Strong oxidizing agents. Oxidizers. Acetic acids Organic acid anhydrides. Powdered metals. Strong acids. Strong bases.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. If heated with peroxides present, violent decomposition can occur.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Aliphatic hydrocarbons	142-82-5	INHALATION LC50 Rat 103 GM/M3
Glycol ether	1569-01-3	DERMAL LD50 Rabbit 3550 mg/kg ORAL LD50 Rat 2504 mg/kg

12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available
Mobility:	No data available

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L No data available
Ether propellant	115-10-6	48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L No data available
Glycol ether	1569-01-3	Aquatic LC50 (96h) Rainbow Trout > 100 mg/L Aquatic LC50 (48h) Daphnia > 100 mg/L 72HR EC50 Algae > 100 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 01/31/2023

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.