# Safety Data Sheet E742 Zero Stick



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

# 1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566	Product Name: Product Code: Product Use:	Zero Stick E742 Mold Release Duster/Freeze Spray
1-800-227-5538	24-hour emergency phone:	1-800-424-9300 [CHEMTREC]
2. HAZARD IDENTIFICATION		
POTENTIAL HEALTH EFFECTS Classification of the chemical in accordance w GHS Hazard Symbols	vith paragraph (d) of §1910.1200;	
	Gases under pressure - Liquified Gas Flammable Aerosol Category 2	
Signal Word	Warning	
	I Statements       Flammable aerosol.         Contains gas under pressure; may explode if heated.	
Precautionary Statements		
	Keep away from heat/sparks/open flames/hot surfaces. Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even afte	
	Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do no expose to temperatures ex	sceeding 50°C/ 122°F.

COMPONENT	rocrbon/ether blend	<u>CAS #</u> 115-10-6		<u>Percent</u> 80-100		
Aliphatic hydroc		142-82-5		1-20		
IMIS® III* HA	ZARDOUS WARNINGS:					
Iealth: 1	Flam	mability: 3	Physical:	1	Personal Protective Equipment:	See Section 8
* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.						
Ĩ	<b>.</b>	02) 462-6272 for more informatio	n on this current rating system	l.		
. FIRST AI	D MEASURES	, 				
I. FIRST AI	D MEASURES	tly with plenty of water for at leas			nptoms persist or there	
• FIRST AI	D MEASURES Immediately flush eyes gen is visual difficulty, seek me In case of contact, immedia	tly with plenty of water for at leas dical attention. tely wash contaminated area with	t 15 minutes while holding eye plenty of water for at least 15	elids apart. If syr minutes. For liqu		
Ĩ	D MEASURES Immediately flush eyes gen is visual difficulty, seek me In case of contact, immedia frostbite if necessary. Seek	tly with plenty of water for at leas dical attention. tely wash contaminated area with medical attention if symptoms per al facility, or poison control center	t 15 minutes while holding eye plenty of water for at least 15 sist. Wash clothing before reus	elids apart. If syr minutes. For liqu se.	id contact, treat for	

NOTES TO PHYSICIAN:

attention.

Stoner Incorporated

E742

PAGE 1

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEA	SURES
Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions. "Empty" containers retain product residue and can be dangerous.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

# 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

## 7. HANDLING AND STORAGE

Handling:	Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Do not breathe vapor.
-	May cause frostbite. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This
	material can be harmful or irritating. Avoid prolonged or repeated contact with skin. Do not pressurize, cut, weld, braze, solder, drill,
	grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or
	death.
Storage:	Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Store away

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Keep from extreme temperatures.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to pa known, suspected or apparent adver	1	imits indicated below in this	s section of the SDS (from
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.			
Skin Protection:	The use of chemically resistant glov skin.	ves is recommended if there	is any possibility of prolong	ged or repeated liquid contact with
Respiratory Protection:	A supplied air respirator should be respirator where there is likelihood			limits. Use NIOSH approved
<u>COMPONENT</u>	<u>CAS #</u>	ACGIH TLV	OSHA PEL	<b>OTHER</b>
Halogenated hydrocrbon/ether	blend 115-10-6	Not established	Not established	1,000 ppm 8 & 12 hr. TWA (Mfr.)
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Appearance: Odor: Odor Threshold: pH: Melting/Freezing Point (°F): Boiling Point (°F):

Flash Point (°F PMCC): Evaporation Rate: Flammability (solid, gas): Percent VOCs (%): Clear Colorless Slight ethereal. Slight Very faint Not applicable No data available No data available Not applicable Not determined

No data available

60 - 80

Aerosol cylinder

Relative Density (H2O=1): Solubility in Water: Partial Coefficient: noctanol/water: Autoignition Temperature (°F): Decomposition Temperature (°F): Viscosity, dynamic (cSt):

Vapor Density [air = 1]:

Lower Flammability Limit (%):

Upper Flammability Limit (%):

Vapor Pressure (PSIG @ 70°F):

Not applicable Not applicable No data available >1 0.84 Not determined Low; 10-49% No data available

Not applicable No data available No data available

### **10. STABILITY AND REACTION**

Nydrofiloric acid and possibly carbonyl fluoride decomposition products.         Conditions to Avoid:       Avoid contact with: Oxidizers. Acetic acids Organic acid anhydrides. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Magnesium, etc. Strong oxidizing agents.         Decomposition Products:       If heated with peroxides present, violent decomposition can occur. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Oxides of phosphorous.	Chemical Stability:	Stable. Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature [>250 C], may form
Decomposition Products: If heated with peroxides present, violent decomposition can occur. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Oxides of	Conditions to Avoid:	flames, sparks, static discharges or glowing metal surfaces. Alkali. Alkaline earth metals. Freshly abraded aluminum
Decomposition Products: If heated with peroxides present, violent decomposition can occur. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Oxides of		
	Decomposition Products:	If heated with peroxides present, violent decomposition can occur. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. Oxides of

Reproductive & Developmental Toxicity:	No data available.		
IARC Carcinogen Designation:	No data available		
Ingredient	CAS #	Toxicological Data	
Halogenated hydrocarbon	811-97-2	INHALATION LC50 Rat 1500 GM/M3	
		INHALATION LC50 Mouse 1700 GM/M3	
Aliphatic hydrocarbons	142-82-5	INHALATION LC50 Rat 103 GM/M3	

# **12. ECOLOGICAL INFORMATION**

Ecological Toxicity: Mobility: Degradability:	Presents little or no hazard to the aquatic environment. No data available Not considered biodegradable; 100% volatile.	
<b>Ingredient</b> Ether propellant	<b>CAS #</b> 115-10-6	<b>Toxicological Data</b> 48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L No data available
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L

### 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

### **14. TRANSPORTATION INFORMATION**

AgencyUN NumberProper Shipping nameHaz.DOTUN1033Dimethyl Ether2.1IATAUN1033Dimethyl Ether2.1IMDGUN1033Dimethyl Ether2.1	ard Class Packing Group Not applicable Not applicable Not applicable
---	---

No data available

### **15. REGULATORY INFORMATION**

 Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

 COMPONENT
 CAS # % BY WEIGHT

 No components listed in this section.
 SARA Section 313

#### **Toxic Substances Control Act**

All components of this product are listed on the TSCA inventory.

#### California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

#### **16. OTHER INFORMATION**

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 07/18/2023

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

PAGE 3