# Safety Data Sheet M205 Silicone Mold Release



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

## 1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy Quarryville, PA 17566 1-800-227-5538		Product Name: Product Code: Product Use: 24-hour emergency phone:	Silicone Mold Release M205 Mold Release 1-800-424-9300 [CHEMTREC]
2. HAZARD IDENTIFIC POTENTIAL HEALTH EFFECT Classification of the chemical in a GHS Hazard Symbols	S		
No. 1	<u>*</u>		!
GHS Classification	Skin Corr	n Hazard Category 1 osion/Irritation Category 2 e Liquid Category 3	•
Signal Word	Danger		
Hazard Statements	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation.		
Precautionary Statements			
Prevention	Keep cont Ground/b P241 - Us Use only Take prec P264 - Wa	y from heat/sparks/open flames/hot surfaces. ainer tightly closed. ond container and receiving equipment. e explosion-proof electrical, ventilating and non-sparking tools. autionary measures against static discharge. ash thoroughly after handling. ective gloves/protective clothing/eye protect	lighting equipment.
Response	P302+P35 IF ON SK P321 - Sp Do NOT i If skin irri	<ul> <li>0 - If swallowed: Immediately call a poison</li> <li>52 - If on skin: Wash with plenty of soap and IN (or hair): Remove/Take off immediately ecific treatment (see on this SDS).</li> <li>induce vomiting.</li> <li>tation occurs: Get medical advice/attention.</li> <li>78 - In case of fire: Use proper media to extir</li> </ul>	d water. all contaminated clothing. Rinse skin with water/shower.
Storage	Keep cont	ainer tightly closed. well-ventilated place. Keep cool.	
Disposal	Dispose o wastes.	f contents/container in accordance with loca	nl/regional/national/international regulation for hazardous

3. COMPOSITION/INFORMATION ON INGREDIENTS						
COMPONENT Petroleum distillates	<u>CAS #</u> 64741-65-7			<u>Percent</u> 90 - 99		
HMIS® III* HAZARDOUS WA Health: 1	RNINGS: Flammability: 2		Physical:	0	Personal	See Section 8
Stoner Incorporated	M205	PAGE 1				

\* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

### 4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there
Claim Countrate	is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.
NOTES TO DUNG	

#### NOTES TO PHYSICIAN:

\_

This material is an aspiration hazard. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions);

5. FIRE FIGHTING MEASURES				
Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a combustible liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other			
Fire Fighting Instructions:	flames and ignition sources at locations distant from the material's handling point. Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self- contained breathing apparatus.			

# 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

### 7. HANDLING AND STORAGE

Handling: All 5 gallon and larger containers should be grounded and/or bonded when material is transferred.Do not use near ignition sources. Avoid prolonged or repeated contact with skin.

Storage: Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to pr		imits indicated below in	this section of the SDS (from
	known, suspected or apparent adver	se effects).		
Eye Protection:	Wear chemically resistant safety gla	sses with side shields when	handling this product. W	/ear additional eye protection such as
	chemical splash goggles and/or face	shield when the possibility	exists for eye contact wi	th splashing or spraying liquid or
	airborne material. Have an eye wasl	n station available.		
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with			
	skin.			
Respiratory Protection:	Use NIOSH approved respirator wh	ere there is likelihood of inl	halation of the product m	ist, spray or aerosol. A supplied air
1 5	respirator should be used if ventilation	ion is not sufficient to maint	ain exposure limits.	
COMPONENT	CAS #	ACGIH TLV	<b>OSHA PEL</b>	OTHER
Petroleum distillates	64741-65-7	100 ppm TWA	500 ppm	Not established

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk liquid	Lower Flammability Limit (%):	0.6
Appearance:	Clear Colorless	Upper Flammability Limit (%):	7
Odor:	Petroleum solvent	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density $[air = 1]$ :	>1
pH:	Not applicable	Relative Density (H2O=1):	0.78
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Not determined
Boiling Point (°F):	No data available	Partial Coefficient: n- octanol/water:	No data available
Flash Point (°F PMCC):	120	Autoignition Temperature (°F):	500
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas): Percent VOCs (%):	No data available 90 - 99	Viscosity, dynamic (cSt):	No data available

# **10. STABILITY AND REACTION**

Chemical Stability: Conditions to Avoid:

Decomposition Products:

Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.

Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

# 11. TOXICOLOGICAL INFORMATION

Stable.

Reproductive & Developmental Toxicity: IARC Carcinogen Designation:	No data available. No data available	
Ingredient Petroleum distillates	<b>CAS #</b> 64741-65-7	Toxicological Data Dermal LD50 > 2000 mg/kg Oral LD50 Rat > 2000 mg/kg Inhalation LC50 (4h) Rat > 10 MG/L

### 12. ECOLOGICAL INFORMATION

Ecological Toxicity: Mobility:

Petroleum distillates

Ingredient

No data available CAS # 64741-65-7

No data available

Toxicological Data Aquatic LC50 Bl gill > 1000 MG/L 24HR EC50 Daphnia > 1000 MG/L 24HR EC50 AQUATIC PLANTS > 1000 MG/L

### 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

### 14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1268	Petroleum distillates, n.o.s. (contains Mineral Spirits)	3	III
IATA	UN1268	Petroleum distillates, n.o.s. (contains Mineral Spirits)	3	III
IMDG	UN1268	Petroleum distillates, n.o.s. (contains Mineral Spirits)	3	III

### 15. REGULATORY INFORMATION

 Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:
 COMPONENT
 CAS #
 % BY WEIGHT
 Regulatory Body

 No components listed in this section.
 SARA Section 313

#### **Toxic Substances Control Act**

All components of this product are listed on the TSCA inventory.

#### California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

### **16. OTHER INFORMATION**

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 08/02/22

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.