

## Safety Data Sheet

### P59101 Kantstik® Sealer 1.0

# Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

#### 1. IDENTIFICATION

Stoner Incorporated  
1070 Robert Fulton Hwy.  
Quarryville, PA 17566  
1-800-227-5538

Product Name: Kantstik® Sealer 1.0  
Product Code: P59101  
Product Use: Mold Release  
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

#### 2. HAZARD IDENTIFICATION

##### POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



##### GHS Classification

Flammable Liquid Category 1  
Aspiration Hazard Category 1  
Skin Corrosion/Irritation Category 2  
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

##### Signal Word

Danger

##### Hazard Statements

Extremely flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
May cause drowsiness or dizziness.

##### Precautionary Statements

###### Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating and lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.

###### Response

P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.  
P302+P352 - If on skin: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312 - Call a poison center, doctor or medical center if you feel unwell.  
P321 - Specific treatment (see on this SDS).  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/attention.

P370+P378 - In case of fire: Use proper media to extinguish.

###### Storage

Keep container tightly closed.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

###### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>Percent</u>
Aliphatic hydrocarbon	64742-48-9	40 - 60
Aliphatic hydrocarbons	142-82-5	20 - 40
Ester	Mixture	3 - 7
Petroleum distillates	MIXTURE	1 - 5
Acetate ester C9-11 alcohol branched (BP 428-482°F)	108419-34-7	0.1- 0.99

#### HMIS® III\* HAZARDOUS WARNINGS:

Health: 1	Flammability: 3	Physical: 0	Personal Protective Equipment:	See Section 8
-----------	-----------------	-------------	--------------------------------	---------------

\* See [www.paint.org/hmis](http://www.paint.org/hmis) or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

### 4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion:	Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison control center immediately. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

#### NOTES TO PHYSICIAN:

This material is an aspiration hazard. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; central nervous system; auditory system; arrhythmias (irregular heartbeats);

### 5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous.
Fire Fighting Instructions:	Use CO <sub>2</sub> , foam or dry chemical. Do not direct a solid stream of water or foam into hot burning pools, this may cause frothing and increase fire intensity. Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Apply water from a safe distance to cool container and protect surrounding area.

### 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

### 7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation.
Storage:	Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Protect from atmospheric moisture.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol. No respiratory protection required under normal conditions of use.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Aliphatic hydrocarbon	64742-48-9	Not established	Not established	196 ppm mfr. recommend
Aliphatic hydrocarbons	142-82-5	400 ppm TWA	Not established	Not established
Ester	Mixture	Not established	50 ppm	Not established
Petroleum distillates	MIXTURE	Not established	300 ppm 300ppm	Not established
Acetate ester C9-11 alcohol branched (BP 428-482°F)	108419-34-7	Not established	Not established	Not established

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk liquid	Lower Flammability Limit (%):	0.7
Appearance:	Clear Colorless	Upper Flammability Limit (%):	6.7
Odor:	Light Hydrocarbon	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Moderate	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H2O=1):	0.69
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Negligible; 0-1%
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	15.8	Autoignition Temperature (°F):	474
Evaporation Rate:	0.1-0.5 (n-Butyl acetate = 1)	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	1.21
Percent VOCs (%):	60 - 80		

## 10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Strong oxidizing agents. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

## 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Aliphatic hydrocarbons	142-82-5	Inhalation LC50 Rat 103 GM/M3

## 12. ECOLOGICAL INFORMATION

Ecological Toxicity:	May cause long-term adverse effects in the aquatic environment.
Mobility:	No data available
Degradability:	This product is expected to be inherently biodegradable.

<u>Ingredient</u>	<u>CAS #</u>	<u>Toxicological Data</u>
Aliphatic hydrocarbon	64742-48-9	LLO- 96HR Rainbow Trout 1000 mg/L ELO- 48HR Daphnia < 1000 mg/L ELO-72HR Algae 1000 mg/L
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L No data available

## 13. DISPOSAL CONSIDERATIONS

Disposal :	Dispose according to Federal, State and local regulations.
------------	--

#### 14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1866	Resin Solution	3	II
IATA	UN1866	Resin Solution	3	II
IMDG	UN1866	Resin Solution	3	II

#### 15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

##### Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

##### California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

#### 16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 09/22/20

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.